

KORY RUNNING GEAR means big load hauling with rugged dependability. For years this running gear has proven itself "best in the field". It provides maximum stability, short turning radius, auto type steering and heavy duty tapered roller bearings. Unique Kory tow-bar is adjustable to a variety of lengths. Strong box girder design and heavy duty reach braces provide excellent strength for big loads. All are designed for non-highway use at tractor speeds.



SPECIFICATIONS

CAPACITY	12 TON MODEL 8278	12 TON TANDEM MODEL 6278	15 TON TANDEM MODEL 8578
TREAD	78"	78"	78"
AXLES	4 X 8 X ³ / ₁₆ " Structural Steel Tubing	4 X 8 X ³ / ₁₆ " Structural Steel Tubing	4 X 8 X ³ / ₁₆ " Structural Steel Tubing
REACH	3" x 1/4" Wall x 6'	3" x 1/4" Wall x 7'	3" x 1/4" Wall x 7'
REACH EXTENSION (STD.)	77 1/2" - 117 1/2"	85 1/2" - 125 1/2"	85 1/2" - 125 1/2"
8' REACH (OPT.)	101 1/2" - 141 1/2"	97 1/2" - 137 1/2"	97 1/2" - 137 1/2"
12' REACH (OPT.)	149 1/2" - 189 1/2"	145 1/2" - 185 1/2"	145 1/2" - 185 1/2"
TIE RODS	1 1/4" x ¹ / ₃₂ " Wall Steel Tubing	1 1/4" x ¹ / ₃₂ " Wall Steel Tubing	1 1/4" x ¹ / ₃₂ " Wall Steel Tubing
TIE ROD ENDS	Heavy Duty Truck Type	Heavy Duty Truck Type	Heavy Duty Truck Type
SPINDLES	2 1/4" Carbon Steel	2" Carbon Steel	2 1/4" Carbon Steel
BEARINGS	Tapered Roller - Inner & Outer	Tapered Roller - Inner & Outer	Tapered Roller - Inner & Outer
HUBS	Heavy Duty 8 Bolt	Heavy Duty 6 Bolt	Heavy Duty 8 Bolt
BOLSTER STAKE	7 Ga. Adj 38" x 42"	7 Ga. Adj 38" x 42"	7 Ga. Adj 38" x 42"
TONGUE (OPT.)	A101	A101	A101
OPTIONAL WHEELS	10 X 16, 10 X 15, 8.25 X 22.5	8 X 15, 8 X 16, 10 X 15, 10 X 16	10 X 16, 10 X 15
WEIGHT WITH RIMS & TONGUE (APPROX **)	900 LBS	1200 LBS	1500 LBS

** WEIGHTS VARY WITH CHOICE OF TONGUE AND RIM SIZE

A101	Heavy Duty Quick Hitch, 1" King Pin, Tapered 8 x 75-1/2", adjusts to 97"
------	--

KORY FARM EQUIPMENT, LLC

P.O. Box 349, Manlius, IL 61338 Phone (815) 445-3711, Fax (815) 445-5141
www.koryfarm.com